

WEBCON

AI Proxy Self-hosted

2026.2.306.71.

history of changes for version 2026.2.306.71.

1. New features

- Added a stateless AI Agent API (v6). WEBCON now stores the agent session state and sends it with every call, allowing any AI Proxy instance to handle any step of a session, for example behind a load balancer. Update AI Proxy before switching WEBCON to the v6 API.
- Added support for tooltips (descriptions) on Item list columns in AI Process Builder. Tooltips can be added, changed, and removed using a prompt.

2. Improvements

- Improved handling of HTTP 429 (Resource exhausted) responses from AI providers. When a specific model is selected, AI Proxy retries the request on that model up to three times with a backoff, and then falls back to the other models configured for the operation. Requests with attachments, as well as AI Concierge and AI Agent requests, fall back only to models of the same provider type. The last model in the queue retries the request with exponential backoff before returning an error. The response includes the identifier of the model that actually handled the request.
- Improved cleanup of AI resources: a failure affecting one item no longer stops the cleanup of the remaining items, resources that have already been deleted are skipped, and unused AI Agent and AI Concierge vector stores are automatically removed after 1 hour.
- AI Process Builder now updates Item list columns in place: changing a column type or reordering columns updates the Item list instead of removing and re-creating it.
- The AI Process Builder change summary is now a short report of the changes actually made, with correct element names and no additional suggestions. It also includes paths removed together with a deleted step.

3. Bug fixes

- Fixed web search grounding for AI Agent with OpenAI models.
- Fixed an issue in AI Process Builder where a request to change or delete a non-existent Item list, column, or form field could modify or delete a different instance of the process.
- Fixed saving AI Process Builder changes when generated names or descriptions exceeded the length limits; they are now shortened to the allowed length.
- Fixed the "Could not find Item list column with id = -1" error and missing Item lists when AI Process Builder creates a form with several Item lists from an attached file.

WEBCON

AI Proxy Self-hosted

2026.2.277.65.

history of changes for version 2026.2.277.65.

1. New features

- Added support for the Gemini 3.x model family through the EU multi-region Vertex AI endpoint. The models are available across all AI features.
- Added support for thought signatures in Chat with Tools, enabling multi-step tool calls with Gemini 3.x models.
- Added action generation in AI Process Builder: actions on steps and paths can now be planned and created based on a prompt or an attached file.

2. Improvements

- Updated the expiration dates of Gemini models.
- When generating application metadata from BPMN files, AI Process Builder now sends a concise transcription of the process to the model instead of the raw XML, significantly reducing token usage and response time.
- Limited the thinking budget for Gemini models, which reduces response times, including in AI Process Builder when processing BPMN files.
- The "All connectors attempts failed" error message now includes the last error and the connector type (for example, an HTTP 429 response from the provider).
- Shortened the names and descriptions generated in AI Process Builder.

3. Bug fixes

- Fixed token counting for Gemini models: thinking tokens are now included in usage in line with how Google bills them.
- Fixed identifiers for parallel calls to the same tool in Gemini responses.
- Fixed text being lost when a Gemini response also contains tool calls.

WEBCON

AI Proxy Self-hosted

2026.2.260.63.

history of changes for version 2026.2.260.63.

1. New features

- Added a step-by-step generation flow to AI Process Builder in API v5, with separate endpoints for creating a session, running an individual tool, and generating a comment. This allows the client to display progress and retry a single step. The previous endpoint remains available and is now marked as legacy.
- Added model selection (`modelId`) to AI Process Builder v4 endpoints. The model selected when a thread is created is used for all subsequent calls within that thread.
- Added model selection (`modelId`) to v4 endpoints for sentiment analysis, summaries, and prompts used by business rules.
- Added support for Item list form fields in AI Process Builder, including columns, column types, and validation.
- Added support for the form field matrix in AI Process Builder, including Item list columns and column permissions.
- Added deterministic parsing of BPMN diagrams in AI Process Builder. The process structure is read without using the model, while the model is responsible for merging and naming steps.
- The AI Agent can now use data from static files attached to the process.
- Added file descriptions and categories to the attachment context passed to the model.
- Added a Helm chart for running AI Proxy Self-hosted in Kubernetes clusters, including k3s and AKS.

2. Improvements

- AI Proxy Self-hosted now supports JWT authentication using `ClientId/ClientSecret` as an alternative to mTLS, as well as separate certificates for each role (HTTPS, mTLS, JWT).
- The Helm chart now supports:
 - switching between mTLS and JWT,
 - separate certificates for each role,
 - secrets supplied through Kubernetes Secrets instead of being entered directly in the configuration,
 - HTTPS-only communication,
 - value validation before deployment.
- AI Concierge now sets Choice field values only when they are directly supported by the source content, instead of inferring them from loose associations.
- AI Concierge and the AI Agent now take into account instructions from the process designer included in field descriptions when filling in the form.
- AI translations are now retried and switched to a fallback provider separately for each batch. A batch rejected with HTTP 429 is immediately passed to the next provider, while other errors are retried up to 3 times, so a single failed batch is no longer omitted from the result.
- Disabled model thinking for basic AI operations (sentiment, summary, prompt, translation, audio transcription, and file analysis), which significantly reduces response times for models with thinking enabled.
- Model thinking in Gemini models is now limited to 2048 tokens. This makes processing times more predictable, including when generating a process in AI Process Builder from a BPMN file.
- When generating AI Process Builder metadata from BPMN files, a compact transcription of the process is sent to the model instead of the raw XML, which significantly reduces token usage and response time.
- The AI Process Builder workflow generator no longer leaves empty phases that were not part of the application description.
- The AI Process Builder workflow generator now places negative end steps after positive ones.

3. Bug fixes

- Gemini thinking tokens are now included in token usage. The provider bills them as output tokens, so reported usage may be higher than before.
- Fixed errors in AI Agent and AI Concierge when using Azure AI Foundry models (HTTP 404 "Response not found").
- Fixed BPMN conversion:
 - gateways involving human decisions were converted into separate steps instead of paths,
 - return paths to merged steps were lost.
- Fixed AI Concierge and AI Agent leaving Yes/No fields empty when the model returned values such as Tak, yes, or 1.
- Fixed AI Concierge integration with LiteLLM:
 - responses with empty token counters were rejected,
 - inline attachments were sent incorrectly,

WEBCON

AI Proxy Self-hosted

2026.2.135.35.

history of changes for version 2026.2.135.35.

1. New features

- Added a web-based administration interface for configuring AI providers, connections, and models. The interface is always available in self-hosted mode.
- Added a configurable timeout for connections to AI providers (`TimeoutSeconds`). When the timeout is exceeded, the call is aborted and the request is forwarded to the next configured model.

2. Improvements

- Updated the Gemini integration by replacing the previous library with the Google Gen AI SDK.
- Updated the default model configuration by adding Gemini 2.5 Pro and defining expiration dates for Gemini models scheduled for retirement.
- Improved how the AI process design assistant (Designer Desk) reproduces workflows and data models described in attached files. The assistant now faithfully reproduces the attached definition instead of adding unspecified fields, and each file is processed only once, reducing token usage.
- Improved the prompts used by the AI process design assistant and switched the assistant to the Gemini 2.5 Flash model.
- Added scripts and documentation for building and running AI Proxy locally in self-hosted mode using Docker. The resources are available in the `WEBCON-BPS/WebCon-AiProxy-GettingStarted` repository.

3. Bug fixes

- Fixed fallback to the next provider when a model repeatedly returned rate-limit errors (429). After all retries are exhausted, the request is now forwarded to the next model instead of failing.
- Fixed an issue where the AI process design assistant generated unwanted workflow elements or form fields when the task concerned only one of these areas. Design tools are now selected based on the content of the task.
- Fixed inconsistent references between phases, steps, paths, and data sources in AI process design commands after identifier reassignment, as well as a unique identifier error that occurred when adding elements.
- Fixed an issue where the AI process design assistant duplicated the start step and phases instead of updating the existing elements. Generated path names were also corrected.
- Fixed an error when parsing the `PickersToSet` collection in AI process design commands.
- Fixed incorrect collection creation in AI translations when using the gpt-4.1-mini model.
- Fixed an error when retrieving an AI Proxy token caused by a missing limit value in the database.
- Fixed model configuration binding and loading when communicating with AI models through a proxy running in self-hosted mode.
- Fixed a "Parameter cannot be null" error in the end-of-day session cleanup job.

WEBCON

AI Proxy Self-hosted

2026.2.64.17.

history of changes for version 2026.2.64.17.

1. New features

- Added handling for models marked as expired, allowing AI Proxy to correctly recognize models that should no longer be used.
- Added model selection support in v4 endpoints for AI Concierge, translations, transcriptions, and AI Agent sessions.
- Added information about the model used to the AI operation result.
- Added an endpoint for retrieving available models together with their identifiers.
- Added `Chat with Tools` support for OpenAI and Gemini models.
- Added an OpenAI API-compatible connector, enabling integration with LiteLLM, LM Studio, OpenRouter and similar providers.
- Added inline file upload support for OpenAI, Azure, Gemini, and the OpenAI API-compatible connector.
- Added support for Azure authentication with `DefaultAzureCredential` as an alternative to API key authentication.
- Added OIDC support in services using the OpenAI client.

2. Improvements

- Improved AI Proxy configuration loading and validation, including support for model identifiers and provider configuration.
- Renamed `MethodType` to grouping `AiTaskType` in `aiconfiguration.json` to better reflect the purpose of the configured AI operation.
- Renamed the `Authorization` node to `OidcAuthorization` to make the OIDC authorization configuration more explicit.
- Aligned the behavior of the OpenAI API-compatible connector with OpenAI handling, including cleanup mechanisms and file handling.
- Improved API key passing and handling in services using OpenAI.
- Added logging of the model used to process an AI request.
- Improved cancellation handling in `Chat with Tools`.
- Improved AI Concierge responses during navigation and enhanced handling of content returned by tools.

3. Bug fixes

- Fixed an issue with uploading files to Azure by switching to the OpenAI client.
- Fixed .txt attachment handling in Gemini chat conversations.
- Fixed file handling in the OpenAI connector.
- Fixed AI Concierge command parsing in the OpenAI API-compatible connector.
- Fixed an exception caused by a missing API key in `OpenAiService`.
- Fixed v4 endpoints handling when the `method` parameter is missing.
- Fixed prompt handling in selected AI Concierge scenarios.
- Fixed the transcription name in the enum.
- Improved error logging when loading the AI configuration.

WEBCON

AI Proxy Self-hosted

2026.1.27.108.

history of changes for version 2026.1.27.108.

1. New features

- Added the Concierge v3 endpoint with support for navigation tools, making **AI Concierge** available across the entire Portal, where it can assist users with navigation and suggest moving to the appropriate locations. The actual navigation is performed after the user clicks the navigation button. Support was also extended to include the `//goto` command, which forces the use of the navigation mechanism. This change requires WEBCON version 2026.1.6 or later to work.

WEBCON

AI Proxy Self-hosted

2026.1.24.106

history of changes for version 2026.1.24.106

1. New features

- Added support for the Azure AI Foundry connector in AI Proxy, together with AI Connector logic. Clarified the requirements for Azure-side resource configuration and network access needed to run and test the integration locally.
- Changed the version numbering scheme for AI Proxy Self-hosted. The version number is now calculated automatically and indicates compatibility with a specific WEBCON version.

WEBCON

AI Proxy Self-hosted

1.0.0.235

history of changes for version 1.0.0.235

1. New features

- Released **AI Proxy Self-hosted** — a new component that enables customers to use AI functionality in WEBCON based on their own infrastructure, completely bypassing WEBCON infrastructure. The solution is available under the Enterprise subscription license and the perpetual WEBCON Agentic AI Framework license.

AI Proxy Self-hosted can be installed in the customer's environment (on-premise or private cloud), with the option to connect and configure the customer's own AI models — hosted in Google Vertex, OpenAI, or Azure AI Foundry. This gives customers full control over the data and infrastructure used for AI processing, making it easier to meet security requirements, privacy policies, and industry regulations.

A dedicated AI Proxy Self-hosted mode has been introduced, along with a new configuration node for this mode, added to the `appsettings.json` configuration files used to run AI Proxy, including:

- the option to enable Azure Key Vault for storing sensitive data,
- a variable storing the path to a .pem or .pfx certificate along with its password.

An alternative class implementation has also been prepared which, in this mode, allows Azure Key Vault to be replaced with environment variables.

A new, unified AI Proxy Self-hosted provider-configuration model based on priorities has been designed and released. It allows defining multiple providers, automatically switching to lower-priority providers, and assigning different AI models to specific methods (text, image, and audio models). The configuration is defined in the `aiconfiguration.json` file, which is loaded when the AI Proxy application starts.

The ability to select the application's operating mode in the configuration file has been added, along with support for local certificates (.pem/.pfx) used to sign and verify access tokens — without the need to communicate with external authorization services (including LAS) or databases. In AI Proxy Self-hosted mode, dependencies on external infrastructure components have been reduced: the application can run without connections to licensing services, databases, or cloud data stores, and the required mechanisms are automatically selected based on configuration.